



DOWNLOAD: <https://tinurdi.com/2ihme6>



xtest.exe C:\Program Files\icom IC-2200H-C Programmer\XTEST.EXE /T 9 691.08 29.00 0.42 The /T option specifies that you wish to complete a single program. You also need to know that you can only complete one program at a time. When you have finished programming the IC-2200H IC, press Enter. 4. Program a second IC using the same program as previously outlined. Important: You must re-enter the correct programming data in the SW1 (SW) box. Step 1 Select the P and T area and click on the [P/T] button and then click the [PROGRAM] button. Step 2 Enter the Programming data (program number followed by a space then the 8 hex digits) in the respective boxes (see the box on page 49). Step 3 Enter the SPI mode and select the test mode as per the box on page 48. Step 4 Program the second IC using the same program as outlined on pages 46-49. When you have finished programming the IC, press Enter. 5. View the latest programming data entered on the CRT display. Step 1 Select the P and T area and click on the [P/T] button and then click the [MONITOR] button. Step 2 Enter the correct IC program number in the appropriate boxes. Step 3 The LCD screen will display the programming data and the programming time. Step 4 Press ENTER and you will then see the status of the IC as programmed (see the following illustration). \*\*IC PROGRAM:\*\* \*\*PROGRAM TYPE:\*\* \*\*PROGRAM ID:\*\* \*\*CRC ERRORS:\*\* \*\*CRC ERROR:\*\* \*\*PROGRAM MINUTE:\*\* \*\*PROGRAM SECOND:\*\* \*\*DONE:\*\* \*\*MONITOR:\*\* \*\*TRUE:\*\* \*\*FALSE:\*\* \*\*CRC:\*\* \*\*0:\*\* \*\*ON:\*\* \*\*N/A:\*\* \*\*PROGRAMMING DONE:\*\* \*\*TIME PASSED:\*\* \*\*PROGRAMMING TIME (MINUTE):\*\* \*\*PROGRAMMING TIME (SECOND):\*\* \*\*DONE:\*\* Now you have successfully 82157476af

[Autodata340rtorrent](#)  
[spider man movie in punjabi download](#)  
[Stardeck Icon Packager v5.10.032.Keymaker.AND.Patch.RNDD.Setup.Free](#)